

Tumble dryer

T5250

Features and benefits

- High productivity – 2 full loads per hour
- Low energy consumption for optimal efficiency
- Large door opening for easy loading and unloading
- Large selfcleaning lint screen for easy maintenance
- Reversible door hanging for a convenient laundry flow
- Easy access to vital parts from front and rear for simple servicing
- With Compass Pro program control
 - Large display and one control knob for easy program selection
 - Language selection
 - Quick selection and option buttons for the most frequently used drying programs and options
 - Drying program packages optimized for Economy, Care and Time and option buttons for selection of dryness
 - Service program for adjustment of parameters
 - USB connection
- The coin version with Ecopower to avoid over drying of the garments and get a lower energy consumption

Main options

- Stainless steel front
- Stainless steel drum
- Residual Moisture Control – RMC
- Reversing drum
- Payment: coinmeter with Ecopower, chipcard reader, CP connection
- Special versions (dryer + option package): Lagoon® variant includes stainless steel front, stainless steel drum, RMC and reversing drum
- Fresh air intake
- Supply disconnecter
- CMIS (Certus Management Information System)



Images shown are a representation of the product only and variations may occur.

Main specifications			T5250				
Rated capacity, filling factor 1:18		kg/lb	13.9/30.7				
	filling factor 1:22	kg/lb	11.4/25.1				
Drum volume		litre	250				
Drum diameter		mm	760				
Heating,	electric	kW	6.0/9.0/13.2/13.5				
	gas	BTU/h (kW)	46000 (13.5)				
	steam at 800 kPa		25.0				
Consumption data*			6.0 kW**	9.0 kW	13.5 kW	Gas	Steam
Total time full load	min		36	36	27	27	18
Energy consumption full load	kWh		3.9	5.5	5.8	6.2	13
Evaporation	g/min		111	160	214	211	326
Energy kWh/litre water evaporated	kWh/l		0.98	0.95	1.02	1.09	2.23
* At rated capacity 1:22, 100% cotton load at 50% initial moisture dried to 0%.							
** Test load 8.2 kg/18lb							

Electrical connections					
Heating alternative	Main voltage		Heating power kW	Total power kW	Recommended fuse A
		Hz			
Electric heated	220-240V 1 -	50/60	6.0	7.1	35
	220-240V 3 -	50/60	9,0/13,5	10,1/14,6	35/50
	380-415V 3N -	50/60	9,0/13,5	10,1/14,6	16/25
	440V 3 -	60	9,0/13,5	10,1/14,6	16/25
	480V 3 -	60	9,0/13,5	10,1/14,6	16/20
115V 3 -	60	13.2	14.3	80	
Gas heated/ Steam heated	220-240V 1 -	50/60	-	1.1	10
	220-240V 3 -	50/60	-	1.1	10
	380-415V 3N -	50/60	-	1.1	10
	440V 3 -	60	-	1.1	10
	480V 3 -	60	-	1.1	10

Steam, gas and air connections			T5250	
Steam	ISO 7/1-R		1"	
Steam pressure		kPa	100-1000	
Steam consumption		kg/h	65	
Condensate	ISO 7/1-R		1"	
Gas	ISO 7/1-R		1/2"	
Gas pressure	Natural gas	Pa	2000	
		mbar	20	
	Propane	Pa	2800-5000	
		mbar	28-50	
Air outlet		ø mm	200	
Evacuated air,	el 6/9 kW	m ³ /h	360	
			el 13.5 kW	600
			gas 13.5 kW	600
			steam	1000
Pressure drop	el 6/9 kW	Max. Pa	650	
			el/gas 13.5 kW	520
			el 18 kW/gas 21 kW/steam	270
Sound levels				
Airborne sound level		dB(A)	<70	
Heat emission				
% of installed power, max			15	
Shipping data*				
Weight		net, kg	167	
Shipping volume		crated, m ³	1.62	
Dimensions in mm				
A	Width		790	
B(a)	Depth, el and gas		958	
B(b)	Depth, steam		1125	
C	Height		1770	
D			785	
E			840	
F			108	
G			66	
H			278	
I			171	
J			172	
K			395	
L			605	
M			747	
N			711	
1	Operating panel			
2	Door opening ø 580 mm			
3	Electrical connection			
4	Gas connection			
5	Exhaust connection			
6	Steam: in			
7	Steam: out			

* Average data. Crated weight/shipping volume depends on configuration. Please contact logistics for exact measures.

